

Timely Verification at Large-scale Gas Centrifuge Enrichment Plants

Mark Walker, CVT Graduate Associate

CVT Workshop 2016
Ann Arbor, MI



CONSORTIUM *for* VERIFICATION TECHNOLOGY



What do ongoing trends in gas centrifuge enrichment technology mean for IAEA safeguards?

–

What can the IAEA do to keep pace with these trends?



BACKGROUND

WHERE ARE THE GOALPOSTS?

Comprehensive Safeguards Agreements (NNWS), Voluntary Offer Agreements (NWS)

HSP

Hexapartite Safeguards Project (1980-1983)

- Goals: Detect diversion of declared material AND facility misuse
- Traditional item-based safeguards measures
- Limited Frequency Unannounced Access (LFUA) to cascade halls

Continuous enrichment monitoring (1995), environmental sampling (1996), AP (1997-)

RMA

Revised Model Approach (2006)

- Additional goal: Detect excess LEU production using undeclared material
- Short-notice random inspections (SNRIs) to feed/withdrawal areas to verify that only declared material is fed



WHAT HAS CHANGED SINCE 2006?



Pre-Fukushima: Construction of new GCEPs, Expansion of existing ones

- New plants: URENCO USA (4.7 MSWU), Georges-Besse II (7.5 MSWU)
- Expansions: Gronau UTA II (2.4 MSWU), Almelo expansion (1.8 MSWU)



Post-Fukushima: 60 MSWU supply glut accumulates

- This LEU is somewhere... not necessarily in UF_6 , however.

Bottom line: More capacity per site, More LEU in storage



What IAEA safeguards issues do these dynamics raise?



What IAEA safeguards issues do these dynamics raise?

Timely detection of HEU production



What IAEA safeguards issues do these dynamics raise?

Timely detection of HEU production

Efficiency of traditional SG measures



What IAEA safeguards issues do these dynamics raise?

Timely detection of HEU production

Efficiency of traditional SG measures



What might an HEU production scenario look like at a modern commercial GCEP?



SIMULATING A MISUSE SCENARIO

SMITH, LEBRUN & LABELLA, JNMM 2013:

	#	tSWU/year
GCEP	1	4000
Units/GCEP	8	500
Cascades/Unit	10	50


Further assumed here:

- 1000 Centrifuges/Cascade: 50 kgSWU/yr
- 11 enriching stages, 4 stripping stages
- Max enrichment = 5%
- 10 g U/centrifuge
- Separation factor $\gamma = R'/R'' = 1.44$




VISUALIZING A MISUSE SCENARIO

A NOTIONAL (5-CASCADE) PRODUCTION UNIT:




VISUALIZING A MISUSE SCENARIO

A NOTIONAL (5-CASCADE) PRODUCTION UNIT:




VISUALIZING A MISUSE SCENARIO

A NOTIONAL (5-CASCADE) PRODUCTION UNIT:



VISUALIZING A MISUSE SCENARIO

A NOTIONAL (5-CASCADE) PRODUCTION UNIT:



IS IT WORTH RESHAPING CASCADES?

IN THIS CASE, PROBABLY NOT.

TRADEOFFS OF NO RESHAPING

Pros: Expedient, Simple, Additional enrichment gain from off-normal stage cuts


Cons: Some loss of nominal SWU capacity

3 CASCADE GROUPS (2 IN MODIFIED UNIT)

	Feed Enrichment	Product Enrichment	Tails Enrichment	tSWU/year
Original	0.72%	5.11%	0.29%	50
Mid Group	5.11%	34.0%	2.29%	49.5
Top	34.0%	94.1%	28.1%	28.4



EQUILIBRATION IS QUICK.





5% → 34%

9 cascades



EQUILIBRATION IS QUICK.




5% → 34%

9 cascades




EQUILIBRATION IS QUICK.



5% → 34%

9 cascades



34% → 94%

1 cascade



PRODUCTION RATE ESTIMATES

MODE 1: No LEU sitting around

While continuously producing LEU in unmodified units:

- 1 modified unit: ~0.5 SQ/day
- 2 modified units: ~1.0 SQ/day



PRODUCTION RATE ESTIMATES

MODE 1:

No LEU sitting around

While continuously producing LEU in unmodified units:

- 1 modified unit: ~0.5 SQ/day
- 2 modified units: ~1.0 SQ/day

MODE 2:

LEU sitting around

Modifying all 8 units and feeding them with on-hand LEU:

- 10.8 SQ in 3 days
- With 2x tails recycling: 29 SQ in 7 days



PRODUCTION RATE ESTIMATES

MODE 1:

No LEU sitting around

While continuously producing LEU in unmodified units:

- 1 modified unit: ~0.5 SQ/day
- 2 modified units: ~1.0 SQ/day

MODE 2:

LEU sitting around

Modifying all 8 units and feeding them with on-hand LEU:

- 10.8 SQ in 3 days
- With 2x tails recycling: 29 SQ in 7 days

Both modes about a factor of 2 slower than idealized calculations would dictate



PRODUCTION RATE ESTIMATES

MODE 1:

No LEU sitting around

While continuously producing LEU in unmodified units:

- 1 modified unit: ~0.5 SQ/day
- 2 modified units: ~1.0 SQ/day

MODE 2:

LEU sitting around

Modifying all 8 units and feeding them with on-hand LEU:

- 10.8 SQ in 3 days
- With 2x tails recycling: 29 SQ in 7 days

Both modes about a factor of 2 slower than idealized calculations would dictate

Time for a weekend breakout?



What measures can the IAEA apply to detect HEU production in a timely manner?



DETECTING HEU PRODUCTION



Long-standing Measures

- LFUA Inspections
- Environmental Sampling



DETECTING HEU PRODUCTION



Long-standing Measures

- LFUA Inspections
- Environmental Sampling



Newer Unattended Measures (some under development)

- Online Enrichment Monitor (OLEM)
- Authenticated Load Cell Monitoring (LCM)
- Unattended Cylinder Verification Station (UCVS)



DETECTING HEU PRODUCTION



Long-standing Measures

- LFUA Inspections
- Environmental Sampling



Newer Unattended Measures (some under development)

- Online Enrichment Monitor (OLEM)
- Authenticated Load Cell Monitoring (LCM)
- Unattended Cylinder Verification Station (UCVS)

Detecting
signatures of
misuse
'downstream'
from source



DETECTING HEU PRODUCTION



Long-standing Measures

- LFUA Inspections
- Environmental Sampling



Newer Unattended Measures (some under development)

- Online Enrichment Monitor (OLEM)
- Authenticated Load Cell Monitoring (LCM)
- Unattended Cylinder Verification Station (UCVS)

Detecting
signatures of
misuse
'downstream'
from source

Detecting
reconfiguration
itself



DETECTING HEU PRODUCTION



Long-standing Measures

- LFUA Inspections
- Environmental Sampling



Newer Unattended Measures (some under development)

- Online Enrichment Monitor (OLEM)
- Authenticated Load Cell Monitoring (LCM)
- Unattended Cylinder Verification Station (UCVS)



Future Measures

- Unattended means for detecting piping reconfiguration in real time
- Unattended detection of hidden feed/withdrawal points

Detecting
signatures of
misuse
'downstream'
from source

Detecting
reconfiguration
itself



UNATTENDED MEASURES FOR REAL-TIME RECONFIGURATION DETECTION

WITH INTERMITTENT DATA TRANSMISSION TO IAEA HQ



CONSORTIUM *for* VERIFICATION TECHNOLOGY



UNATTENDED MEASURES FOR REAL-TIME RECONFIGURATION DETECTION

WITH INTERMITTENT DATA TRANSMISSION TO IAEA HQ



Electronic, remote-indicating seals on potentially significant sampling ports



UNATTENDED MEASURES FOR REAL-TIME RECONFIGURATION DETECTION

WITH INTERMITTENT DATA TRANSMISSION TO IAEA HQ



Electronic, remote-indicating seals on potentially significant sampling ports



IAEA surveillance cameras at cascade hall access points, and/or on sampling ports



UNATTENDED MEASURES FOR REAL-TIME RECONFIGURATION DETECTION

WITH INTERMITTENT DATA TRANSMISSION TO IAEA HQ



Electronic, remote-indicating seals on potentially significant sampling ports



IAEA surveillance cameras at cascade hall access points, and/or on sampling ports



Open path gas detection systems for HF (more research needed?)



UNATTENDED MEASURES FOR REAL-TIME RECONFIGURATION DETECTION

WITH INTERMITTENT DATA TRANSMISSION TO IAEA HQ



Electronic, remote-indicating seals on potentially significant sampling ports



IAEA surveillance cameras at cascade hall access points, and/or on sampling ports



Open path gas detection systems for HF (more research needed?)



Unattended NDA for detecting HEU presence in process areas

Detector arrays are expensive. How about a roving roomba detector?



FINAL THOUGHTS ON TECHNOLOGY



FINAL THOUGHTS ON TECHNOLOGY

Transmission frequency for new unattended technologies will depend on individual characteristics of GCEPs, and thus the feasibility of various HEU production scenarios.



FINAL THOUGHTS ON TECHNOLOGY

Transmission frequency for new unattended technologies will depend on individual characteristics of GCEPs, and thus the feasibility of various HEU production scenarios.

Data authenticity, accuracy, and security are paramount.



FINAL THOUGHTS ON TECHNOLOGY

Transmission frequency for new unattended technologies will depend on individual characteristics of GCEPs, and thus the feasibility of various HEU production scenarios.

Data authenticity, accuracy, and security are paramount.

Potential synergies of new systems with operator needs should be exploited.

HF Detection -> Safety

Seals on sampling ports -> Insider threat mitigation



SUMMARY



SUMMARY



The Challenge:

- New challenges to safeguards verification have arisen in the last decade, including timely detection of HEU production
- Starting from a normal production scenario, production of an SQ of weapons-grade HEU could take place, conservatively, within a few days




SUMMARY



The Challenge:

- New challenges to safeguards verification have arisen in the last decade, including timely detection of HEU production
- Starting from a normal production scenario, production of an SQ of weapons-grade HEU could take place, conservatively, within a few days



IAEA

International Atomic Energy Agency

Potential Solutions:

- Unattended systems offer some improvements to detection timeliness for HEU production
- Unattended safeguards measures for detecting reconfiguration of piping and undeclared feed/withdrawal could pay further dividends.



CONSORTIUM *for* VERIFICATION TECHNOLOGY

